

LAPAZ ankle occupational shoes

» Shoes » Occupational shoes » Ankle

Technical sheet

LAPAZ ankle occupational shoes

Product code: 4310-OB



upper	cowhide leather NUBUCK in a thickness of 1,9 - 2,1 mm
lining	breathable thermo-insulation MEMBRANE FREE-TEX®
inner insole	HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic
outsole	EVA/RUBBER - resistant to fuel oils, antistatic, antislip, glued construction
size	36 - 49
standard	EN ISO 20347:2012
version	OB E WRU SRA - without steel toe cap, hydrophobic, FREE-TEX®

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	Yes

LAPAZ ankle occupational shoes

» Shoes » Occupational shoes » Ankle

CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	No
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	No
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	No
SRC Antislip resistance SRA + SRB	No
Free-tex Membrane	Yes
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20347:2012
Shoe marking	OB

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	1,14 kg	1,42 kg	270 mm	310 mm	110 mm	565 mm	570 mm	335 mm	15,40 kg	240,0 mm
37	1,17 kg	1,48 kg	270 mm	310 mm	110 mm	565 mm	570 mm	335 mm	15,80 kg	247,0 mm
38	1,22 kg	1,53 kg	270 mm	310 mm	110 mm	565 mm	570 mm	335 mm	16,20 kg	253,0 mm
39	1,26 kg	1,55 kg	270 mm	310 mm	110 mm	565 mm	570 mm	335 mm	16,40 kg	260,0 mm
40	1,28 kg	1,59 kg	270 mm	310 mm	110 mm	565 mm	570 mm	335 mm	16,80 kg	267,0 mm
41	1,30 kg	1,61 kg	270 mm	310 mm	110 mm	565 mm	570 mm	335 mm	17,20 kg	273,0 mm
42	1,31 kg	1,65 kg	290 mm	340 mm	120 mm	610 mm	615 mm	365 mm	18,20 kg	280,0 mm
43	1,37 kg	1,71 kg	290 mm	340 mm	120 mm	610 mm	615 mm	365 mm	18,40 kg	287,0 mm
44	1,43 kg	1,79 kg	290 mm	340 mm	120 mm	610 mm	615 mm	365 mm	19,60 kg	293,0 mm
45	1,48 kg	1,83 kg	290 mm	340 mm	120 mm	610 mm	615 mm	365 mm	19,80 kg	300,0 mm
46	1,52 kg	1,91 kg	305 mm	370 mm	125 mm	650 mm	650 mm	390 mm	20,60 kg	307,0 mm
47	1,54 kg	1,96 kg	305 mm	370 mm	125 mm	650 mm	650 mm	390 mm	20,80 kg	313,0 mm
48	1,58 kg	1,98 kg	305 mm	370 mm	125 mm	650 mm	650 mm	390 mm	21,40 kg	320,0 mm
49	1,59 kg	1,99 kg	305 mm	370 mm	125 mm	650 mm	650 mm	390 mm	21,50 kg	327,0 mm

Business parameters

Tarric	64039113
Country	CN
Weight	1,65 kg
Add Unit	NPR

LAPAZ ankle occupational shoes

» Shoes » Occupational shoes » Ankle

Add Quantity 1