

NORWICH ankle occupational shoes

» Shoes » Occupational shoes » Ankle

Technical sheet

NORWICH ankle occupational shoes

Product code: 5070-02



upper	cowhide leather with pattern in a thickness of 1,8 – 2,0 mm
lining	laminated breathable fabric MESH
inner insole	anatomically shaped from material EVA with a high absorbency, antistatic
outsole	PU/RUBBER – up to 300°C, resistant to fuel oils, antistatic, antislip, double density injection
size	36 – 48
standard	EN ISO 20347:2022
version	O2 FO HRO SR – without steel toe cap and midsole, hydrophobic

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	Yes
WPA Water resistant upper	Yes
HRO Resist. of the outsole against contact heat	Yes
WR Water resistant	No
WRU Water resistant upper	No

NORWICH ankle occupational shoes

» Shoes » Occupational shoes » Ankle

CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	No
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	No
SRB Antislip prop. on smooth steel with glycerol	No
SRC Antislip resistance SRA + SRB	No
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	EN ISO 20347:2022
Shoe marking	O2

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Inner shoe length
36	1,01 kg	1,25 kg	225 mm	315 mm	120 mm	480 mm	600 mm	340 mm	13,20 kg	240,0 mm
37	1,03 kg	1,26 kg	225 mm	315 mm	120 mm	480 mm	600 mm	340 mm	13,40 kg	246,7 mm
38	1,03 kg	1,29 kg	225 mm	315 mm	120 mm	480 mm	600 mm	340 mm	13,80 kg	253,3 mm
39	1,10 kg	1,35 kg	225 mm	315 mm	120 mm	480 mm	600 mm	340 mm	14,40 kg	260,0 mm
40	1,12 kg	1,38 kg	225 mm	315 mm	120 mm	480 mm	600 mm	340 mm	14,60 kg	266,7 mm
41	1,17 kg	1,42 kg	225 mm	315 mm	120 mm	480 mm	600 mm	340 mm	14,80 kg	273,3 mm
42	1,18 kg	1,45 kg	225 mm	315 mm	120 mm	480 mm	600 mm	340 mm	15,20 kg	280,0 mm
43	1,25 kg	1,52 kg	230 mm	330 mm	125 mm	485 mm	620 mm	350 mm	16,00 kg	286,7 mm
44	1,31 kg	1,57 kg	230 mm	330 mm	125 mm	485 mm	620 mm	350 mm	16,60 kg	293,3 mm
45	1,33 kg	1,61 kg	230 mm	330 mm	125 mm	485 mm	620 mm	350 mm	17,00 kg	300,0 mm
46	1,40 kg	1,71 kg	235 mm	350 mm	125 mm	495 mm	650 mm	380 mm	17,60 kg	306,7 mm
47	1,41 kg	1,71 kg	235 mm	350 mm	125 mm	495 mm	650 mm	380 mm	18,40 kg	313,4 mm
48	1,52 kg	1,82 kg	235 mm	350 mm	125 mm	495 mm	650 mm	380 mm	18,80 kg	320,0 mm

Business parameters

Tarric	64039113
Country	CN
Weight	1,45 kg
Add Unit	NPR

NORWICH ankle occupational shoes

» Shoes » Occupational shoes » Ankle

Add Quantity 1