

SINGAPORE outdoor sandal grey

» Shoes » Outdoor shoes » Sandals

Technical sheet

SINGAPORE outdoor sandal grey

Product code: 4625-25



upper	brushed microfiber combined with textile
lining	laminated breathable fabric MESH
inner insole	HI-POLY – anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
outsole	EVA/RUBBER – glued construction
size	36 – 48
usability	shoes suitable for daily wear and outdoor activities
version	grey colour

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	No

SINGAPORE outdoor sandal grey

» Shoes » Outdoor shoes » Sandals

CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	No
P Midsole penetration protection	No
E Energy absorption in the heel area	No
M Instep protection	No
A Antistatic properties	No
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	No
SRB Antislip prop. on smooth steel with glycerol	No
SRC Antislip resistance SRA + SRB	No
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Inner shoe length
36	0,60 kg	0,83 kg	210 mm	310 mm	110 mm	445 mm	575 mm	340 mm	10,90 kg	240,0 mm
37	0,63 kg	0,86 kg	210 mm	310 mm	110 mm	445 mm	575 mm	340 mm	11,00 kg	247,0 mm
38	0,65 kg	0,89 kg	210 mm	310 mm	110 mm	445 mm	575 mm	340 mm	11,10 kg	253,0 mm
39	0,68 kg	0,90 kg	210 mm	310 mm	110 mm	445 mm	575 mm	340 mm	11,20 kg	260,0 mm
40	0,70 kg	0,93 kg	210 mm	310 mm	110 mm	445 mm	575 mm	340 mm	11,30 kg	267,0 mm
41	0,72 kg	0,98 kg	230 mm	335 mm	120 mm	490 mm	630 mm	355 mm	11,40 kg	273,0 mm
42	0,76 kg	1,03 kg	230 mm	335 mm	120 mm	490 mm	630 mm	355 mm	11,60 kg	280,0 mm
43	0,79 kg	1,06 kg	230 mm	335 mm	120 mm	490 mm	630 mm	355 mm	11,80 kg	286,0 mm
44	0,83 kg	1,10 kg	230 mm	335 mm	120 mm	490 mm	630 mm	355 mm	12,20 kg	293,0 mm
45	0,87 kg	1,16 kg	240 mm	360 mm	125 mm	510 mm	650 mm	390 mm	12,80 kg	300,0 mm
46	0,90 kg	1,19 kg	240 mm	360 mm	125 mm	510 mm	650 mm	390 mm	13,00 kg	306,0 mm
47	0,93 kg	1,21 kg	240 mm	360 mm	125 mm	510 mm	650 mm	390 mm	13,20 kg	313,0 mm
48	0,96 kg	1,25 kg	240 mm	360 mm	125 mm	510 mm	650 mm	390 mm	13,40 kg	320,0 mm

Business parameters

Tarric	64041990
Country	CN
Weight	1,03 kg
Add Unit	NPR
Add Quantity	1