

WELLINGTON high heel occupational shoes

» Shoes » Occupational shoes » Boots

Technical sheet

WELLINGTON high heel occupational shoes

Product code: 4390-OB



upper	brushed cowhide suede leather VELOUR in a thickness of 1,7 - 1,9 mm
lining	textile, thermo-insulation fleece
inner insole	HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic
outsole	EVA/RUBBER - antislip, glued construction
size	38 - 48
standard	EN ISO 20347:2012
version	OB E SRA - without steel toe cap

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	No

WELLINGTON high heel occupational shoes

» Shoes » Occupational shoes » Boots

CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	No
P Midsole penetration protection	No
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	No
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	No
SRC Antislip resistance SRA + SRB	No
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20347:2012
Shoe marking	OB

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
38	1,51 kg	1,91 kg	340 mm	360 mm	120 mm	620 mm	730 mm	340 mm	20,90 kg	254,0 mm
39	1,52 kg	1,92 kg	340 mm	360 mm	120 mm	620 mm	730 mm	340 mm	21,10 kg	261,0 mm
40	1,57 kg	1,95 kg	340 mm	360 mm	120 mm	620 mm	730 mm	340 mm	21,40 kg	269,0 mm
41	1,59 kg	2,00 kg	340 mm	360 mm	120 mm	620 mm	730 mm	340 mm	21,90 kg	277,0 mm
42	1,66 kg	2,07 kg	340 mm	360 mm	120 mm	620 mm	730 mm	340 mm	22,60 kg	282,0 mm
43	1,84 kg	2,11 kg	350 mm	370 mm	135 mm	675 mm	770 mm	370 mm	25,00 kg	290,0 mm
44	1,91 kg	2,37 kg	350 mm	370 mm	135 mm	675 mm	770 mm	370 mm	25,80 kg	299,0 mm
45	2,30 kg	2,50 kg	350 mm	370 mm	135 mm	675 mm	770 mm	370 mm	27,20 kg	307,0 mm
46	2,12 kg	2,70 kg	350 mm	370 mm	135 mm	675 mm	770 mm	370 mm	27,90 kg	315,0 mm
47	2,20 kg	2,80 kg	350 mm	370 mm	135 mm	675 mm	770 mm	370 mm	29,10 kg	323,0 mm
48	2,30 kg	2,88 kg	350 mm	370 mm	135 mm	675 mm	770 mm	370 mm	29,60 kg	333,0 mm

Business parameters

Tarric	64039193
Country	CN
Weight	2,07 kg
Add Unit	NPR
Add Quantity	1